

## Astaro Security Gateway Comparison Chart:

ASG models	<b>110/120</b>	<b>220</b>	<b>320</b>	<b>425</b>	<b>525</b>
<b>Capacity</b>					
Users behind the firewall	10/ Unrestricted	Unrestricted	Unrestricted	Unrestricted	Unrestricted
Firewall throughput (Mbps)	100	260	420	1200	3000
VPN throughput (Mbps)	30	150	200	265	400
VPN tunnels	Unrestricted	Unrestricted	Unrestricted	Unrestricted	Unrestricted
Policies	Unrestricted	Unrestricted	Unrestricted	Unrestricted	Unrestricted
Concurrent connections	60 000	400 000	550 000	700 000	>1 000 000
<b>Hardware Specifications</b>					
Form factor	Desktop	1U Rackmount	1U Rackmount	1U Rackmount	2U Rackmount
Memory	256 MB	512 MB	1 GB	2 GB	4 GB
Hard drive	20 GB	40 GB	80 GB	74 GB (S-ATA)	2 x 120 GB / RAID 1**
Hardware acceleration	-	-	-	Yes	Yes
10/100 ethernet ports	3	8	4	-	1
10/100/1000 ethernet ports	-	-	4	4 PCI, 4 PCI-Express	10 / 4*
GB SFP ports	-	-	-	-	0 / 6*
USB ports	2	2	4	4	2
COM ports	-	2	2	2	2
VGA port	1	-	-	-	1
PS/2 keyboard/mouse port	1	-	-	-	-
LCD display	-	1	1	1	1
Dimensions W x H x D (mm)	177 x 51 x 229	426 x 43.5 x 305	426 x 43.5 x 380	426 x 43.5 x 432	424 x 88 x 600
Weight	2 kg/ 4.4lbs	5 kg/ 11 lbs	7 kg/ 15.4 lbs	7.2 kg/ 15.9 lbs	15 kg/ 33lbs
AC input voltage	100-240 VAC	-	-	-	-
AC input current	2.5 A	-	-	-	-
AC/DC	-	90-264 VAC	90-264 VAC	90-264 VAC	90-264 VAC
Frequency	50-60 Hz	47-63 Hz	47-63 Hz	47-63 Hz	47-63 Hz
Power dissipation	60 W Max	-	-	-	-
ATX Power Supply	-	180 W	150 W	250 W	460 W
Operating temperature	0°C-40°C	0°C-40°C	0°C-40°C	0°C-40°C	0°C-40°C
Storage temperature	-20°C-80°C	-20°C-80°C	-20°C-80°C	-20°C-80°C	-20°C-80°C
Humidity	10%-90% non-condensing	10%-90% non-condensing	10%-90% non-condensing	10%-90% non-condensing	10%-90% non- condensing
Regulatory	FCC/CE certified	FCC/CE certified	FCC/CE certified	FCC/CE certified	FCC/CE certified